



Assembly Guide

TIPS

To detach the parts from the board, press the anchor point with your thumb.
 Always push with your thumb on the engraved side of the board, so the piece falls under the board.
 You can easily locate the anchors points by looking at the back of the board.
 Use PVA glue diluted with a little water. (3 parts adhesive, 1 part of water).
 Use a small file to remove the anchor points' residues. You can also use a modeler's knife (handle it carefully to prevent injury).
 Use a small brush to spread the diluted glue.



Guide Injury counters



Lay a little glue under the small wheel with the numbers.



Jam between your fingers, the roulette that serves as bottom with the large roulette that has numbers. The goal is to make sure they are centered with each other.



Place the small wheel (the one under which you put the glue) into the hole of the large wheel, press a few seconds and remove the large wheel. Clean any excess glue that may prevent the large wheel from turning when you replace it.



Lay a little glue under the small round part (1cm diameter) that has a rectangular hole the same size as the small roulette.



Slide the foot of the symbol (or the small part that replaces it) into the small round slot.



By using this piece, you will be able to stick the small circle well centered on the top of the small roulette wheel.



Remove the symbol, as it is not yet time to glue it.

Painting



This is the time to paint your model and be careful not to spread too much paint on the sides of the wheels, as this may prevent you from finishing the assembly or even prevent the wheels from turning easily.



Once your model is dry, replace the large wheel and the "lid" on top. Finally, glue the symbol into its hole or the nut for the simple kit in the hole.



For the model with the skull, you have some additional cartons parts that form the front and back of the skull.