

TRANCE X ADVANCED E+ 1

GIANT



CARACTÉRISTIQUES TECHNIQUES

TECHNOLOGIE HYBRIDE	
MOTEUR	SyncDrive Pro, 85Nm, powered by Yamaha
CONTRÔLE	RideControl Ergo 3, grip integrated
ÉCRAN	RideControl GO, frame integrated LED displayANT+ Wireless display compatible
BATTERIE	EnergyPak Smart 62S, EnergyPak Plus, 250Wh range extender compatible
CADRE	
TAILLES	S, M, L, XL
COULEURS	Panther Green
CADRE	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
FOURCHE	Fox 36 Live Valve, 150mm travel, 44mm offset, Grip2 damper, Boost 110x15QR, electronic adaptive suspension, e-bike integrated, e-bike integrated
AMORTISSEUR (SHOCK)	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated
COMPOSANTES	
GUIDON	Giant Contact 35 Trail, 35x780mm
POIGNÉES	Giant Tactal Pro-E, single lock-on
POTENCE	Giant Contact SL 35
TIGE DE SELLE	Giant Contact Switch, dropper, 30,9mm (S:125, M:150, L/XL:170)
SELLE	Giant Romero, Neutral
PÉDALES	Flat pedal
TRANSMISSION (DRIVETRAIN)	
MANETTES	Shimano Deore XT
DÉRAILLEUR AVANT	MRP HD2 co-moulded chain guide
DÉRAILLEUR ARRIÈRE	Shimano Deore XT, 12-speed, Shadow+
FREINS	Shimano Deore, BR-M6120, 4-piston, hydraulic disc, 203mm
LEVIERS DE FREIN	Shimano Deore, BL-MT6100
CASSETTE	Shimano HG-M6100, 10-51T, 12-speed
CHAÎNE	KMC e.12 Turbo, EcoProteq, e-bike optimized
PÉDALIER	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor = 168, XS/S:160, M/L:165, XL:170)
BOÎTIER DE PÉDALIER	-

ROUES	
JANTES	Giant AM 29", Tubeless ready, 30mm inner width
MOYEURS	Shimano Deore XT, Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAYONS	Sapim E-Lite [r] Race [f]
PNEUS	Maxxis Assegai 29x2.6" foldable, Tubeless, EXO, 3c MaxxTerra[F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 120tpi 3C [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSOIRES	
ÉCLAIRAGE	Optional:- Giant Recon series e-bike lights available and direct connectable

Prix de détail: 9 999 \$

GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur du tube de selle (mm)	400	425	450	475				
Angle du tube de selle	77,2°	78,0°	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°
Longueur du tube supérieur (top tube) (mm)	577	575	607	605	637	635	667	665
Longueur du tube de direction (head tube) (mm)	95	100	110	120				
Angle du tube de direction	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°	65,8°	66,5°
Déport (rake) de fourche (mm)	44	44	44	44				
Trail (mm)	117	122,4	117	122,4	117	122,4	117	122,4
Empattement (mm)	1220	1221	1239	1237	1268	1269	1300	1301
Longueur des bases (mm)	473	473	473	473	473	473	473	473
Hauteur du boîtier de pédalier (mm)	30	20	30	20	30	20	30	20
Portée Verticale (Stack) (mm)	606	601	611	605	621	614	630	624
Portée Horizontale (Reach) (mm)	439	447	457	462	482	489	510	517
Hauteur du cadre (mm)	740	746	727	734	718	726	715	723
Largeur du Guidon (mm)	780	780	780	780				
Longueur de la Potence (mm)	40	40	50	50				
Longueur des manivelles (mm)	160	165	165	170				
Diamètre des Roues	29"	29"	29"	29"				

GIANT Canada se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.