

DEVOTE 2



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Gleaming Olive
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
COMPONENTS	
HANDLEBAR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Cork Tape w/ Gel VLT004-02
STEM	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEATPOST	Giant D-Fuse, alloy
SADDLE	Liv Grit
DRIVETRAIN	
SHIFTERS	Shimano CUES U3030, 2x9
FRONT DERAILLEUR	Shimano CUES U6030
REAR DERAILLEUR	Shimano CUES U4020
BRAKES	Shimano Mechanical Disc Brake BR-RS305 SUPER SLR, [F]160mm, [R]160mm
BRAKE LEVERS	Shimano CUES U3030
CASSETTE	Shimano CS-LG300, 11x36
CHAIN	KMC X11 with Missing Link
CRANKSET	Shimano FC-U6030, 32/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant S-X2 Disc, alloy
HUBS	Giant alloy, 12mm thru-axle
SPOKES	stainless steel
TIRES	Giant CrossCut AT 2, tubeless, 700x38c
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
LIMITS	
MAX TIRE CLEARANCE	53mm

Suggested Retail Price (CDN): \$1,799.00

FRAME GEOMETRY

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390		420		465		500	
Seat Tube Angle	74.5° 74.4°		74.5° 74.4°		74.5° 74.4°		74.5° 74.4°	
Top Tube Length (mm)	525 525		535 535		545 545		555 555	
Head Tube Length (mm)	90		110		140		160	
Head Tube Angle	70.0° 69.9°		70.5° 70.4°		71.0° 70.9°		71.0° 70.9°	
Fork Rake (mm)	50		50		50		50	
Trail (mm)	78.4 82		75 78.5		71.6 75.1		71.6 75	
Wheelbase (mm)	1017 1027		1024 1034		1031 1041		1043 1052	
Chain Stay Length (mm)	430 440		430 440		430 440		430 440	
Bottom Bracket Drop (mm)	80 81		80 81		80 81		80 81	
Stack (mm)	523 524		544 545		574 575		593 594	
Reach (mm)	380 379		384 383		386 385		391 389	
Stand Over Height (mm)	681 688		708 715		748 755		779 786	
Handlebar Width (mm)	400		400		420		420	
Stem Length (mm)	50		60		70		80	
Crank Length (mm)	165		170		172.5		172.5	

All prices and specifications are subject to change without notice.