

Warmall Model#	Length		Power	Resistance	Current	120 Volt Guides	
						3"	4"
						14.8w/sq.ft	11.1w/sq.ft
	ft	m	W	Ω	A	Sq.ft.	Sq.ft.
FC-120V-011	35	10.7	130	110.8	1.1	8.8	11.7
FC-120V-018	60	18.3	220	65.5	1.8	15	20
FC-120V-025	85	26	315	45.7	2.6	21.3	28.3
FC-120V-028	93	28.4	344	41.9	2.9	23.3	31
FC-120V-033	110	33.6	410	35.1	3.4	27.5	36.7
FC-120V-041	135	41.2	500	28.8	4.2	33.8	45
FC-120V-044	146	44.6	540	26.7	4.5	36.5	48.7
FC-120V-048	160	48.8	590	24.4	4.9	40	53.3
FC-120V-054	180	54.9	665	21.7	5.5	45	60
FC-120V-057	189	57.7	699	20.6	5.8	47.3	63
FC-120V-061	200	61	740	19.5	6.2	50	66.7
FC-120V-076	250	76.2	920	15.7	7.7	62.5	83.3
FC-120V-083	275	83.9	1020	14.1	8.5	68.8	91.7
FC-120V-091	300	91.5	1110	13	9.3	75	100
FC-120V-103	350	106.7	1300	11.1	10.8	87.5	116.7
FC-120V-121	400	122	1480	9.7	12.3	100	133.3
FC-120V-136	450	137.2	1670	8.6	13.9	112.5	150
FC-120V-145	480	146.4	1780	8.1	14.8	120	160

Warmall Model#	Length		Power	Resistance	Current	240 Volt Guides	
						3"	4"
						3	4
						14.8w/sq.ft	11.1w/sq.ft
	ft	m	W	Ω	A	Sq.ft.	Sq.ft.
FC-240V-021	70	21.4	260	221.5	1.1	17.5	23.3
FC-240V-028	93	28.4	344	41.9	2.9	23.3	31
FC-240V-036	120	36.6	440	130.9	1.8	30	40
FC-240V-044	146	44.6	540	26.7	4.5	36.5	48.7
FC-240V-052	170	51.9	630	91.4	2.6	42.5	56.7
FC-240V-057	189	57.7	699	20.6	5.8	47.3	63
FC-240V-067	220	67.1	820	70.2	3.4	55	73.3
FC-240V-082	270	82.3	1000	57.6	4.2	67.5	90
FC-240V-097	320	97.6	1180	48.8	4.9	80	106.7
FC-240V-109	360	109.8	1330	43.3	5.5	90	120
FC-240V-121	400	122	1480	38.9	6.2	100	133.3
FC-240V-151	500	152.4	1840	31.3	7.7	125	166.7
FC-240V-167	550	167.7	2040	28.2	8.5	137.5	183.3
FC-240V-182	600	182.9	2220	25.9	9.3	150	200
FC-240V-212	700	213.4	2600	22.2	10.8	175	233.3
FC-240V-242	800	243.9	2960	19.5	12.3	200	266.7
FC-240V-272	900	274.4	3340	17.2	13.9	225	300
FC-240V-291	960	292.7	3560	16.2	14.8	240	320