

# 3.7 WATT- 120V

25-Year

LIMITED WARRANTY



## Cable with plastic guide

Refer to page 3 for installation under soft surfaces.

Model	Length		Spacing (ft <sup>2</sup> )			Watt	Amp	Ohms
			3"	4"	5"			
	Ft.	M	14.8 W	11.2 W	8.9 W			
3,7GCWC-120V-05	16.5	5.05	4.1	5.5	6.9	60	0.5	240.0
3,7GCWC-120V-10	33	10.1	8.3	11.0	13.8	120	1.0	120.0
3,7GCWC-120V-14	49.5	15.1	12.4	16.5	20.6	180	1.5	80.0
3,7GCWC-120V-19	66	20.1	16.5	22.0	27.5	240	2.0	60.0
3,7GCWC-120V-24	82.5	25.1	20.6	27.5	34.4	300	2.5	48.0
3,7GCWC-120V-29	99	30.2	24.8	33.0	41.3	360	3.0	40.0
3,7GCWC-120V-34	115.5	35.2	28.9	38.5	48.1	420	3.5	34.3
3,7GCWC-120V-38	132	40.2	33.0	44.0	55.0	480	4.0	30.0
3,7GCWC-120V-43	148.5	45.3	37.1	49.5	61.9	540	4.5	26.7
3,7GCWC-120V-48	165	50.3	41.3	55.0	68.8	600	5.0	24.0
3,7GCWC-120V-58	198	60.4	49.5	66.0	82.5	720	6.0	20.0
3,7GCWC-120V-67	231	70.4	57.8	77.0	96.3	840	7.0	17.1
3,7GCWC-120V-77	264	80.5	66.0	88.0	110.0	960	8.0	15.0
3,7GCWC-120V-87	297	90.5	74.3	99.0	123.8	1080	9.0	13.3
3,7GCWC-120V-96	330	100.6	82.5	110.0	137.5	1200	10.0	12.0
3,7GCWC-120V-106	363	110.6	90.8	121.0	151.3	1320	11.0	10.9
3,7GCWC-120V-115	396	120.7	99.0	132.0	165.0	1440	12.0	10.0
3,7GCWC-120V-125	429	130.8	107.3	143.0	178.8	1560	13.0	9.2
3,7GCWC-120V-135	462	140.8	115.5	154.0	192.5	1680	14.0	8.6
3,7GCWC-120V-144	495	150.9	123.8	165.0	206.3	1800	15.0	8.0

120 V

Includes cable, one floor sensor and plastic cable guides



# 3.7 WATT - 240V

## Cable with plastic guide

Refer to page 3 for installation under soft surfaces.

FLOOR HEATING SYSTEMS

240 V

Model	Length		Spacing (ft <sup>2</sup> )			Watt	Amp	Ohms
			3"	4"	5"			
	Ft.	M	14.8 W	11.2 W	8.9 W			
3,7GCWC-240V-10	33.0	10.1	8.3	11.0	13.8	120	0.5	480.0
3,7GCWC-240V-14	49.5	15.1	12.4	16.5	20.6	180	0.8	320.0
3,7GCWC-240V-19	66.0	20.2	16.5	22.0	27.5	240	1.0	240.0
3,7GCWC-240V-24	82.5	25.1	20.6	27.5	34.4	300	1.3	192.0
3,7GCWC-240V-29	99.0	30.2	24.8	33.0	41.3	360	1.5	160.0
3,7GCWC-240V-34	115.5	35.2	28.9	38.5	48.1	420	1.8	137.1
3,7GCWC-240V-38	132.0	40.2	33.0	44.0	55.0	480	2.0	120.0
3,7GCWC-240V-43	148.5	45.3	37.1	49.5	61.9	540	2.3	106.7
3,7GCWC-240V-48	165.0	50.2	41.3	55.0	68.8	600	2.5	96.0
3,7GCWC-240V-53	175.0	53.3	43.8	58.3	72.9	650	2.7	88.6
3,7GCWC-240V-58	198.0	60.4	49.5	66.0	82.5	720	3.0	80.0
3,7GCWC-240V-63	208.0	63.4	52.0	69.3	86.7	770	3.2	74.8
3,7GCWC-240V-67	231.0	70.4	57.8	77.0	96.3	840	3.5	68.6
3,7GCWC-240V-72	238.0	72.5	59.5	79.3	99.2	880	3.7	65.5
3,7GCWC-240V-77	264.0	80.4	66.0	88.0	110.0	960	4.0	60.0
3,7GCWC-240V-82	271.0	82.6	67.8	90.3	112.9	1000	4.2	57.6
3,7GCWC-240V-87	297.0	90.6	74.3	99.0	123.8	1080	4.5	53.3
3,7GCWC-240V-96	330.0	100.6	82.5	110.0	137.5	1200	5.0	48.0
3,7GCWC-240V-106	363.0	110.6	90.8	121.0	151.3	1320	5.5	43.6
3,7GCWC-240V-115	396.0	120.8	99.0	132.0	165.0	1440	6.0	40.0
3,7GCWC-240V-126	429.0	130.8	107.3	143.0	178.8	1560	6.5	36.9
3,7GCWC-240V-135	462.0	140.8	115.5	154.0	192.5	1680	7.0	34.3
3,7GCWC-240V-145	479.0	146.0	119.8	159.7	199.6	1770	7.4	32.5
3,7GCWC-240V-154	528.0	161.0	132.0	176.0	220.0	1920	8.0	30.0
3,7GCWC-240V-173	594.0	181.0	148.5	198.0	247.5	2160	9.0	26.7
3,7GCWC-240V-192	660.0	201.2	165.0	220.0	275.0	2400	10.0	24.0
3,7GCWC-240V-212	726.0	221.2	181.5	242.0	302.5	2640	11.0	21.8
3,7GCWC-240V-231	792.0	241.4	198.0	264.0	330.0	2880	12.0	20.0
3,7GCWC-240V-250	858.0	261.5	214.5	286.0	357.5	3120	13.0	18.5
3,7GCWC-240V-270	924.0	281.6	231.0	308.0	385.0	3360	14.0	17.1
3,7GCWC-240V-289	990.0	301.8	247.5	330.0	412.5	3600	15.0	16.0

Includes cable, one floor sensor and plastic cable guides